

## MODEL C PERMANENT PACKER

### PRODUCT 20-042

The **TechWest C Permanent Packer** is an economical, large-bore, Permanent Packer, designed specifically for dual zone gas well completions and rated for 45,000 kPa (6,500 PSI) differential pressure.

The packer may be wireline set using an E-4 Setting Assembly, or hydraulically set on tubing using a B Setting Tool (or equivalent). The 114 mm C Permanent Packer may be set on endless tubing using an N Setting Tool (or equivalent).

The C Permanent Packer features one-piece opposing slips, which combine to ensure a solid reliable pack off.

### OPERATION

The Model C Packer is set either hydraulically using a TechWest Model B Setting Tool (Product 10-270 and 10-271) and L Setting Adapter (Product 10-073) or on wireline using a Baker E-4 Setting Assembly.

Wireline/E-line allows for setting under pressure in a live well without the need for a snubbing or when the setting interval is tight and a precise landing depth is necessary.

The Model C may be removed by milling over and then retrieving.

### SPECIFICATIONS

20-042 SPECIFICATION GUIDE						
Size	Weight		Model C Product No.	Seal Bore ID		Nok-Out Product No
	lb/ft	kg/m		in	mm	
4 1/2 114.3	9.5 - 11.6	14.1 - 17.2	<b>20-042-0460</b>	2.390	60.7	20-049-0239
5 1/2 139.7	13.0 - 17.0	19.3 - 25.3	<b>20-042-0560</b>	3.000	76.2	20-049-0300

