

HYDRAULIC TUBING ANCHOR

PRODUCT 20-333

The **TechWest Hydraulic Tubing Anchor** is a retrievable anchor catcher designed to hold the tubing string in tension or compression. No tubing manipulation is needed to set the anchor. Applying tubing pressure against a temporary plug run below the anchor catcher sets the catcher. Once set, bi-directional slips anchor the tubing to prevent upward or downward movement during rod pumping and to prevent tubing from falling if it should part. The anchor catcher is released by straight-pull shear.

FEATURES

- Hydraulic set
- Bi-directional slips anchor the tubing to prevent upward or downward movement.
- Straight-pull shear release


HYDRAULIC CL TUBING ANCHOR

PRODUCT 20-334

The TechWest TW-CL Hydraulic Set Tubing Anchor is identical to the TechWest Hydraulic Tubing Anchor except it contains a Control Line passing through the Mandrel. The Control Line may be plugged off when not required.

SPECIFICATIONS

20-334 SPECIFICATION GUIDE										
CASING		ANCHOR								
Size	Weight	Product Number	OD		ID		Standard Connection		Cont'l Line	
in/mm	lbs/ft		in	mm	in	mm	in	mm	in	mm
7 177.8	32.0-35.0	20-334-0700	5.812	147.6	2.441	62.0	2 7/8	73.0	1/4	6.4
	26.0-29.0	20-334-0710								
	20.0-26.0	20-334-0720	6.060	153.9	2.992	76.0	3 1/2	88.9	1/4	6.4
	17.0-20.0	20-334-0730								
9 5/8 244.5	32.3-53.5	20-334-0950	8.260	209.8	2.992	76.0	3 1/2	88.9	1/4	6.4



SPECIFICATIONS

20-233 SPECIFICATION GUIDE										
Casing			Anchor							
Size	Weight		Product Number	Gauge		ID		Connection		
in / mm	lbs/ft	kg/m		in	mm	in	mm	in	mm	
4	11.6	17.3	20-333-1940	3.328	84.5	1.61	40.9	1.9	48.3	
101.6	9.5	14.1	20-333-2340	3.42	86.9	1.938	49.2	2.375	60.3	
4 1/2	9.5-13.5	14.1-20.1	20-333-2344	3.7	94	1.938	49.2	2.375	60.3	
114.3			20-333-2345	3.771	95.8					
5	20.8	31	20-333-2349	3.917	99.5	1.938	49.2	2.375	60.3	
127	15.0-18.0	22.3-26.8	20-333-2350	4.125	104.8					
	11.5-13.0	17.1-19.3	20-333-2351	4.25	108					
5 1/2	20.0-23.0	29.8-34.2	20-333-2355	4.5	114.3	1.938	49.2	2.375	60.3	
	15.5-20.0	23.1-29.8	20-333-2356	4.641	117.9					
	13.0-14.0	19.3-20.8	20-333-2357	4.781	121.4					
	15.5-20.0	23.1-29.8	20-333-2756	4.641	117.9					
139.7	13.0-14.0	19.3-20.8	20-333-2757	4.781	121.4	2.375	60.3	2.875	73	
5 3/4	17.0-19.5	25.3-29.0	20-333-2758	4.95	125.7	2.375	60.3	2.875	73	
146.1	28.0-32.0	41.7-47.6	20-333-2766	5.484	139.3	2.375	60.3	2.875	73	
	168.3	24.0-28.0	35.7-41.7	20-333-2767	5.625					142.9
7	32.0-35.0	47.6-52.1	20-333-2770	5.812	147.6	2.5	63.5	2.875	73	
	177.8	26.0-29.0	38.7-43.2	20-333-2771	5.958					151.6
		20.0-26.0	29.8-38.7	20-333-2772	6.078					154.4
	17.0-20.0	25.3-29.8	20-333-2773	6.266	159.2	3	76.2	3.5	88.9	
	32.0-35.0	47.6-52.1	20-333-3570	5.812	147.6					
	26.0-29.0	38.7-43.2	20-333-3571	5.958	151.6					
	20.0-26.0	29.8-38.7	20-333-3572	6.078	154.4					
17.0-20.0	25.3-29.8	20-333-3573	6.266	159.2						
7 5/8	33.7-39.0	50.1-58.0	20-333-2775	6.453	163.9	2.5	63.5	2.875	73	
	24.0-29.7	35.7-44.2	20-333-2776	6.672	169.5	3	76.2	3.5	88.9	
	193.7	33.7-39.0	50.1-58.0	20-333-3575	6.453					163.9
	24.0-29.7	35.7-44.2	20-333-3576	6.672	169.5					
8 5/8	44.0-49.0	65.5-72.9	20-333-3585	7.312	185.7	3	76.2	3.5	88.9	
	219.1	32.0-40.0	47.6-59.5	20-333-3586	7.531					191.3
		29.0-35.0	43.2-52.1	20-333-3588	7.856					199.5
	20.0-28.0	29.8-41.7	20-333-3587	7.781	197.6					
9 5/8	47.0-53.5	69.9-79.6	20-333-2795	8.218	208.7	2.5	63.5	2.875	73	
	244.5	40.0-47.0	59.5-69.9	20-333-2796	8.437	214.3	3	76.2	3.5	88.9
		47.0-53.5	69.9-79.6	20-333-3595	8.218	208.7				
	40.0-47.0	59.5-69.9	20-333-3596	8.437	214.3	4	101.6	4.5	114.3	
	47.0-53.5	69.9-79.6	20-333-4595	8.218	208.7					
	40.0-47.0	59.5-69.9	20-333-4596	8.437	214.3					
29.3-36.0	43.6-53.6	20-333-4597	8.593	218.3						